

## 37201 OS-L8D-NW-RX-B-P1

Oprawa LED podtynkowa

5905339372017



### PRODUCT PARAMETERS:

- Colour:** black  
**Place of assembly:** Recessed mount in the ceiling  
**Place of application:** Indoors  
**Minimum distance from the illuminated object:** 0,5m  
**Compatible with a dimmer:** no  
**The product is not suitable to be covered with a heat-insulating material:** yes  
**Length [mm]:** 595  
**Width [mm]:** 595  
**Height [mm]:** 41  
**Integrated LED light source:** yes  
**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Maximum power [W]:** 31  
**Class of protection against electric shock:** I  
**Lampshade material:** plastic  
**Diode type:** LED SMD  
**Luminous flux of the light fitting [lm]:** 3900  
**Colour temperature:** white  
**Service life [h]:** 50000  
**Luminous-flux-retention factor at the end of rated service life:** L90B10  
**Number of on/off cycles:**  $\geq 30000$   
**Lighting angle [°]:** 80  
**Ambient temperature range to which the product can be exposed:** 5÷25  
**Shade type:** louvre / black  
**Enclosure material:** Metal  
**Connection type:** Self-clamping block  
**Range of sections of wires used [mm<sup>2</sup>]:** 1,5÷2,5  
**Lamp-heating time [s]:**  $\leq 1$   
**Lamp-ignition time [s]:**  $\leq 0,5$   
**IP class:** 20  
**Additional information:** Containing product (CP)

### PARAMETERS FOR LED AND OLED LIGHT SOURCES:

- Correlated colour temperature [K]:** 4000  
**Colour consistency in McAdam ellipses:**  $\leq 3$   
**Colour rendering index:** 80

### LOGISTIC DATA:

- Unit of measurement:** unit

## 37201 OS-L8D-NW-RX-B-P1

Oprawa LED podtynkowa



**Packaging method: 1**

**Number of units in the secondary packaging: 1**

**Number of units in the packaging: 1**

KANLUX S.A. (kat 37201) OS-L8D-NW-RX-B-P1 / Krzywa rozsyłu światła  
(biegunowo)

Oprawa: KANLUX S.A. (kat 37201) OS-L8D-NW-RX-B-P1  
Lampy: 4 x OS-L8D-NW

