

# Kanlux



EAN: 5905339372635

LED power supply unit  
Kanlux 37263 BLINGO DRVM34W ON-OFF



## PRODUCT PARAMETERS

Rated voltage [V]	220-240 AC
Rated frequency [Hz]	50

Date of issue: 23.04.2026, 15:18

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland [kanlux@kanlux.com](mailto:kanlux@kanlux.com)

EN

## PRODUCT PARAMETERS

Rated current [A]	0,17
Rated power [W]	25,5 - 34
Maximum power [W]	34
Place of application	Indoors
IP class	20
Compatible with a dimmer	no
Power supply efficiency [%]	88
$\lambda$	0,97
Range of sections of wires used [mm <sup>2</sup> ]	OUT: 0,2-1,5
Supply-cord type	direct current
Overload protection	yes
Short-circuit protection	yes
Maximum temperature Ta [°C]	40
Input voltage - PRI [V]	220-240
Output voltage - SEC [V]	30-40
Output current - sec [ma]	850
Tc [°C]	75

## DIMENSIONS AND MOUNTING

Height [mm]	28
Width [mm]	42
Length [mm]	118
Connection type	Terminal block
Range of sections of wires used [mm <sup>2</sup> ]	IN: 0,75-1,0

## MATERIAL AND CONSTRUCTION

Colour	white
Material	plastic
Class of protection against electric shock	II

## LOGISTICS

Unit of measurement	unit
Packaging method	50
Number of units in the secondary packaging	1
Number of units in the packaging	50
Net unit weight [g]	80
Grammage [g]	102.2
Gross unit weight [g]	96
Length of a unit pack [cm]	14.5
Width of a unit pack [cm]	6
Height of a unit pack [cm]	3
Weight of a cardboard box [kg]	5.11
Width of a cardboard box [cm]	19.5
Height of a cardboard box [cm]	33
Length of a cardboard box [cm]	32
Volume of a cardboard box [m <sup>3</sup> ]	0.020592

Date of issue: 23.04.2026, 15:18

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com