

37294 IPER LED 10W-NW-L

Ceiling-mounted LED light fitting

5905339372949



The Kanlux IPER LED ceiling fixture has a number of advantages that affect its quality. 5-year warranty, durability 50,000 hours, high luminous efficiency of 120lm/W - these are just some of them. Kanlux IPER LED ceiling lamps are based on components from renowned manufacturers, such as Samsung 2835 LEDs. Moreover, these lamps are characterized by exceptional resistance to the ingress of water and dust IP65 and the highest mechanical resistance IK10 ("vandal proof"), thanks to which you can use this ceiling lamp in every possible place inside and outside. To adapt it to every situation and place, you can choose from: two luminaire shapes, four powers and the option of choosing luminaires with a microwave motion sensor (SE models).

PRODUCT PARAMETERS:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 10

Luminous flux of the light fitting [lm]: 1200

Luminous efficiency of the lamp [lm/W]: 120

Lighting angle [°]: 120

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: 6

Colour temperature: white

Colour rendering index: 80

Service life [h]: 50000

Number of on/off cycles: ≥50000

Diode type: LED SMD

Colour: white

Place of assembly: ceiling mounted, wall mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Width [mm]: 200

Height [mm]: 55

Integrated LED light source: yes


Class of protection against electric shock: II

Lampshade material: plastic

Enclosure material: plastic

37294 IPER LED 10W-NW-L

Ceiling-mounted LED light fitting



Ambient temperature range to which the product can be exposed: -20÷40

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1,5

IK class: 10

IP class: 65

Kształt: square

Additional information: It is not possible to replace the LED light source

Additional information: It is not possible to replace the control panel or control equipment

Additional information: Containing product (CP)

Mercury content: no

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

LED module:

2835_40_40_1500V_1.0_18um_186*186_0.8(mm)_OPS_UL_2_CG-10W

On-mode power of the light source Pon [W]: 8.6

Energy consumption in on-mode of the light source (kWh/1000h): 9

Energy efficiency class of the light source in the contains product (CP): D

Useful luminous flux of the light source Φ_{use} [lm]: 1450

Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)

Height of the light source [mm]: 1

Width of the light source [mm]: 186

Depth of the light source [mm]: 186

Chromaticity coordinates (x): 0,38

Chromaticity coordinates (y): 0,38

Claim of equivalent power [W]: 96

R9 colour rendering index value: 4

Survival factor: 0,9

The lumen maintenance factor: 0,96

Lighting technology used: LED

Non-directional or directional light source: NDLS

Mains or non-mains light source: NMLS

Connected light source (CLS): no

Colour-tuneable light source: no

High luminance light source: no

Anti-glare shield: no

37294 IPER LED 10W-NW-L

Ceiling-mounted LED light fitting

Dimmable: no

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

Net unit weight [g]: 508

Grammage [g]: 660

Length of a unit pack [cm]: 21

Width of a unit pack [cm]: 6.5

Height of a unit pack [cm]: 21

Weight of a cardboard box [kg]: 3.3

Width of a cardboard box [cm]: 23


Height of a cardboard box [cm]: 23.5

Length of a cardboard box [cm]: 32

Volume of a cardboard box [m³]: 0.017296

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website
-



37294 IPER LED 10W-NW-L

Ceiling-mounted LED light fitting

