


37375 ZONA MINI-B/B

PIR motion sensor

5905339373755



PRODUCT PARAMETERS:

Colour: black

Place of assembly: ceiling mounted

Place of application: Indoors

Micro-interval between relay contacts: yes

Height [mm]: 21

Diameter [mm]: 76

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Material: plastic

Ambient temperature range to which the product can be exposed: 5+25

Sensor type: PIR

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 0,75÷1,5

Sensor-operation time [second-minute]: 10-15

sensor working angle [°]: H360

Maximum operating time [min]: 15

Minimum operating time [s]: 10

Maximum power [VA]: 200

Illumination-level setpoint by which the sensor detects movement [lx]: 3-2000

IP class: 20

Sensor range [m]: max 6,5

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 100

Number of units in the secondary packaging: 1

Number of units in the packaging: 100

Net unit weight [g]: 54

Grammage [g]: 86.7

Gross unit weight [g]: 50

Length of a unit pack [cm]: 8

Width of a unit pack [cm]: 3.5

Height of a unit pack [cm]: 8

Weight of a cardboard box [kg]: 8.67

Width of a cardboard box [cm]: 43

Height of a cardboard box [cm]: 19



37375 ZONA MINI-B/B

PIR motion sensor

Length of a cardboard box [cm] : 43.5

Volume of a cardboard box [m³] : 0.03554

Date of issue: 28.03.2025, 10:20

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN