


38044 AL-MS5D-NW-RST-B-NT

Linear LED luminaire

5905339380449





AL-MS-RST-B-NT

**PRODUCT PARAMETERS:****Colour:** black**Place of assembly:** ceiling mounted**Place of application:** Indoors**Minimum distance from the illuminated object:** 0,5m**Compatible with a dimmer:** no**Fixture lighting direction:** down**Length [mm]:** 1140**Width [mm]:** 60**Height [mm]:** 69**Integrated LED light source:** yes**Rated voltage [V]:** 220-240 AC**Rated frequency [Hz]:** 50**Maximum power [W]:** 16**Class of protection against electric shock:** I**Lampshade material:** plastic**Diode type:** LED SMD**Luminous flux [lm]:** 2300**Service life [h]:** 50000**Luminous-flux-retention factor at the end of rated service life:** L90B10**Number of on/off cycles:** ≥30000**Lighting angle [°]:** X60/Y60**Ambient temperature range to which the product can be exposed:** 5÷25**Shade type:** louvre**Enclosure material:** aluminum alloy**Connection type:** Self-clamping block**Range of sections of wires used [mm²]:** 1,5÷2,5**Lamp-heating time [s]:** ≤1**Lamp-ignition time [s]:** ≤0,5**IP class:** 20**Luminous efficiency of the lamp [lm/W]:** 144**PARAMETERS FOR LED AND OLED LIGHT SOURCES:****Correlated colour temperature [K]:** 4000**Colour consistency in McAdam ellipses:** ≤3**Colour rendering index:** 80**LOGISTIC DATA:****Unit of measurement:** unit**Packaging method:** 1

38044 AL-MS5D-NW-RST-B-NT


Linear LED luminaire

**Number of units in the secondary packaging : 1****Number of units in the packaging : 1****Net unit weight [g] : 2042****Grammage [g] : 2370****Gross unit weight [g] : 2370****Length of a unit pack [cm] : 136****Width of a unit pack [cm] : 11****Height of a unit pack [cm] : 7****Weight of a cardboard box [kg] : 2.37****Width of a cardboard box [cm] : 11****Height of a cardboard box [cm] : 7****Length of a cardboard box [cm] : 136****Volume of a cardboard box [m³] : 0.010472****ADDITIONAL INFORMATION:**

- 5 years Warranty under the terms of the warranty statement, available on our website

38044 AL-MS5D-NW-RST-B-NT

Linear LED luminaire

**ACCESSORIES**

32540	ALIN CORD 1F-W	Power supply terminal for ALIN luminaires and tracks, 1-phase, white, 150 cm
32541	ALIN CORD 1F-B	Power supply terminal for ALIN luminaires and tracks, 1-phase, black, 150 cm
32542	ALIN CORD 1F-SR	Power supply terminal for ALIN luminaires and tracks, 1-phase, silver 150 cm
07871	ROPE-NT 150 SINGLE	ROPE-NT 150 SINGLE steel rope (single) for suspending fittings, 2 pcs. in a set