


03835 DB212S 2X12P/SMD

DB-series distribution board

5905339038357



DB series switchboards, meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called “hollow walls” or on technical sections.

PRODUCT PARAMETERS:

Colour: white / grey
Door colour: grey
Place of assembly: wall mounted
Norm: PN-EN 62208
Rated voltage [V]: 230/400 AC
Rated current [A]: 63
Rated frequency [Hz]: 50
Class of protection against electric shock: II
Material: plastic
Number of modules: 2x12P
Temperature resistance [°C]: 650
IK class: 06
IP class: 40
number of rows: 2

LOGISTIC DATA:

Packaging method: 10
Number of units in the secondary packaging: 1
Number of units in the packaging: 10
Net unit weight [g]: 1180
Grammage [g]: 1420
Length of a unit pack [cm]: 33
Width of a unit pack [cm]: 27.5
Height of a unit pack [cm]: 11
Weight of a cardboard box [kg]: 14.2
Width of a cardboard box [cm]: 35
Height of a cardboard box [cm]: 57.5
Length of a cardboard box [cm]: 54.5
Volume of a cardboard box [m³]: 0.109681

03835 DB212S 2X12P/SMD

DB-series distribution board