

38544 KRD10-4/63/100-B

Residual-current circuit breaker, 4P



PRODUCT PARAMETERS

Rated voltage [V]	400 AC
Rated frequency [Hz]	50
Rated current [A]	63
Differential-rated current [mA]	100
Residual-current protection type	B
IP class	20
Norm	PN-EN 61008-1
Terminal capacity – solid conductor [mm ²]	max 25
Terminal capacity – stranded conductor [mm ²]	max 16
Number of modules	4
Rated activation capacity[A]	10000
Rated insulation voltage UI [V]	400
Number of poles	4

DIMENSIONS AND MOUNTING

Height [mm]	86.7
Width [mm]	72

MATERIAL AND CONSTRUCTION

Colour	white
--------	-------

Date of issue: 23.02.2026, 08:27

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

DIMENSIONS AND MOUNTING

Length [mm]	73
Place of assembly	na szynę TH35
Range of sections of wires used [mm ²]	max 25

MATERIAL AND CONSTRUCTION

Ambient temperature range to which the product can be exposed	-25÷40
---	---------------

LOGISTICS

Unit of measurement	unit
Packaging method	3
Number of units in the secondary packaging	3
Number of units in the packaging	30
Net unit weight [g]	402
Grammage [g]	461.33
Gross unit weight [g]	445
Length of a unit pack [cm]	8
Width of a unit pack [cm]	9
Height of a unit pack [cm]	8
Weight of a cardboard box [kg]	13.8399
Width of a cardboard box [cm]	27
Height of a cardboard box [cm]	19
Length of a cardboard box [cm]	49
Volume of a cardboard box [m ³]	0.025137

Date of issue: 23.02.2026, 08:27

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com