

38724 KRD10-2/25/30-AC

Residual-current circuit breaker, 2P
5905339387240




PRODUCT PARAMETERS	
Rated voltage [V]	230 AC
Rated frequency [Hz]	50
Rated current [A]	25
Differential-rated current [mA]	30
Residual-current protection type	AC
IP class	20
Norm	PN-EN 61008-1
Terminal capacity – solid conductor [mm²]	max 25
Terminal capacity – stranded conductor [mm²]	max 16
Number of modules	2
Rated activation capacity[A]	10000
Rated insulation voltage UI [V]	400
Number of poles	2

DIMENSIONS AND MOUNTING	
Height [mm]	81

DIMENSIONS AND MOUNTING

Width [mm]	36
Length [mm]	75
Place of assembly	na szynę TH35
Range of sections of wires used [mm ²]	max 25



MATERIAL AND CONSTRUCTION

Colour	white
Ambient temperature range to which the product can be exposed	-25÷40

LOGISTICS

Unit of measurement	unit
Packaging method	60
Number of units in the secondary packaging	1
Number of units in the packaging	60
Net unit weight [g]	208
Gross unit weight [g]	235.83
Gross unit weight [g]	230
Length of a unit pack [cm]	9
Width of a unit pack [cm]	4
Height of a unit pack [cm]	8
Weight of a cardboard box [kg]	14.1498
Width of a cardboard box [cm]	27
Height of a cardboard box [cm]	19
Length of a cardboard box [cm]	47
Volume of a cardboard box [m ³]	0.024111

Date of issue: 27.08.2026, 15:33

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com