

39110 SOLN LED CCTDIM W/G

Ceiling-mounted LED light fitting

5905339391100



1800K
SUPER
WARM



Kanlux SOLN LED CCT DIM are elegant ceiling-mounted lights combining functionality with decorative character. Equipped with adjustable light colour (2700 K, 4000 K, 6500 K) and a dimming function, they allow you to adjust the lighting to the mood and needs of the moment. With a luminous efficacy of up to 1460 lm, the luminaires guarantee comfortable lighting in both bedrooms and living rooms. An additional advantage is the Night Light mode, which provides soft night light with a colour temperature of 3000 K, and the Sunset Light mode, which fills the interior with soft, warm light inspired by the sunset. This function helps you to calm down after a busy day, creating an atmosphere conducive to rest, relaxation or evening reading. The luminaire has a diameter of 380 mm and subtle colour finishes (white, black, gold), which make SOLN LED a practical and stylish light source.

PRODUCT PARAMETERS:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: max 25
Luminous flux [lm]: max 1460 (4000K)
Lighting angle [°]: 120
Light source: LED
Diode type: LED SMD
Integrated LED light source: yes
Correlated colour temperature [K]: 2700-6500
Colour consistency in McAdam ellipses : 6
Colour temperature: Warm white, white, cold white
Colour rendering index: 90
Service life [h]: 20000
Number of on/off cycles: ≥20000
Colour: white / gold
Place of assembly: ceiling mounted
Place of application: Indoors
IP class: 20
Minimum distance from the illuminated object : 0,5m
Built-in brightness control: yes
Compatible with a dimmer: no
Control: infrared remote control
Height [mm]: 75

Date of issue: 15.09.2025, 16:07


We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

39110 SOLN LED CCTDIM W/G

Ceiling-mounted LED light fitting



Diameter [mm]: 380

Class of protection against electric shock : I

Lampshade material: plastic

Enclosure material: Metal

Night Light function: 13W / 460lm / 2700K

Ambient temperature range to which the product can be exposed: 5÷25

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1,5

Kształt: round

LED light source replaceability: Possibility of replacing the LED light source only by qualified personnel (only by the manufacturer service)

Control gear replaceability: Possibility of replacing the control equipment only by qualified personnel (only by the manufacturer service)

Product category according to 2019/2020/EU: Containing product (CP)

Mercury content: no

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Energy efficiency class of the light source in the contains product (CP): E

Number of modules (LED light source): 4

Useful luminous flux of the light source Φ_{use} [lm]: 600

Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)

Lighting technology used: LED

Non-directional or directional light source : NDLS

Mains or non-mains light source : NMLS

Connected light source (CLS): no

Colour-tunable light source: no

High luminance light source: no

Anti-glare shield: no

Dimmable: no

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 10

Number of units in the secondary packaging : 1

Number of units in the packaging : 10

Net unit weight [g]: 864

39110 SOLN LED CCTDIM W/G

Ceiling-mounted LED light fitting

Grammage [g]:	1252
Length of a unit pack [cm]:	42
Width of a unit pack [cm]:	8.5
Height of a unit pack [cm]:	42
Weight of a cardboard box [kg]:	12.52
Width of a cardboard box [cm]:	45
Height of a cardboard box [cm]:	45
Length of a cardboard box [cm]:	85
Volume of a cardboard box [m³]:	0.172125

Date of issue: 15.09.2025, 16:07

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com