


39341 KMB10-B20/3

Overcurrent circuit breaker, 3P

5905339393418



PRODUCT PARAMETERS:

Rated voltage [V]: 400 AC

Rated frequency [Hz]: 50

Rated current [A]: 20

Place of assembly: na szynę TH35

IP class: 20

Norm: PN-EN 60898-1

Length [mm]: 76

Width [mm]: 52.5

Height [mm]: 82

Ambient temperature range to which the product can be exposed: -5÷40

Range of sections of wires used [mm²]: 1÷25

Terminal capacity – solid conductor [mm²]: max 25

Terminal capacity – stranded conductor [mm²]: max 16

Release characteristics: B

Energy-limit class: 3

Number of modules: 3

Rated short-circuit current [A]: 10000

Rated insulation voltage UI [V]: 500

Number of poles: 3

Mechanical endurance: 10000

Electrical endurance: 4000

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 4

Number of units in the secondary packaging: 4

Number of units in the packaging: 40

Net unit weight [g]: 312

Grammage [g]: 337.25

Gross unit weight [g]: 312

Weight of a cardboard box [kg]: 13.49

Width of a cardboard box [cm]: 25

Height of a cardboard box [cm]: 19

Length of a cardboard box [cm]: 46

Volume of a cardboard box [m³]: 0.02185