


## 39344 KMB10-B25/2

Miniature circuit breaker, 2P

5905339393449



### PRODUCT PARAMETERS:



**Rated voltage [V]:** 230/400 AC

**Rated frequency [Hz]:** 50

**Rated current [A]:** 25

**Place of assembly:** na szynę TH35

**IP class:** 20

**Norm:** PN-EN 60898-1

**Length [mm]:** 76

**Width [mm]:** 35

**Height [mm]:** 82

**Ambient temperature range to which the product can be exposed:** -5÷40

**Range of sections of wires used [mm<sup>2</sup>]:** 1÷25

**Terminal capacity – solid conductor [mm<sup>2</sup>]:** max 25

**Terminal capacity – stranded conductor [mm<sup>2</sup>]:** max 16

**Release characteristics:** B

**Energy-limit class:** 3

**Number of modules:** 2

**Rated short-circuit current [A]:** 10000

**Rated insulation voltage UI [V]:** 500

**Number of poles:** 2

**Mechanical endurance:** 10000

**Electrical endurance:** 4000

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 6

**Number of units in the secondary packaging:** 6

**Number of units in the packaging:** 60

**Net unit weight [g]:** 218

**Grammage [g]:** 235

**Gross unit weight [g]:** 218

**Weight of a cardboard box [kg]:** 14.1

**Width of a cardboard box [cm]:** 25

**Height of a cardboard box [cm]:** 19

**Length of a cardboard box [cm]:** 46

**Volume of a cardboard box [m<sup>3</sup>]:** 0.02185