


## 39386 KMB10-C25/1

Overcurrent circuit breaker, 1P

5905339393869



### PRODUCT PARAMETERS:

**Rated voltage [V]:** 230/400 AC

**Rated frequency [Hz]:** 50

**Rated current [A]:** 25

**Place of assembly:** na szynę TH35

**IP class:** 20

**Norm:** PN-EN 60898-1

**Length [mm]:** 76

**Width [mm]:** 17.5

**Height [mm]:** 82

**Ambient temperature range to which the product can be exposed:** -5÷40

**Range of sections of wires used [mm<sup>2</sup>]:** 1÷25

**Terminal capacity – solid conductor [mm<sup>2</sup>]:** max 25

**Terminal capacity – stranded conductor [mm<sup>2</sup>]:** max 16

**Release characteristics:** C

**Energy-limit class:** 3

**Number of modules:** 1

**Rated short-circuit current [A]:** 10000

**Rated insulation voltage UI [V]:** 500

**Number of poles:** 1

**Mechanical endurance:** 10000

**Electrical endurance:** 4000

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 12

**Number of units in the secondary packaging:** 12

**Number of units in the packaging:** 120

**Net unit weight [g]:** 104

**Grammage [g]:** 112.5

**Gross unit weight [g]:** 104

**Length of a unit pack [cm]:** 2

**Width of a unit pack [cm]:** 7.2

**Height of a unit pack [cm]:** 8.5

**Weight of a cardboard box [kg]:** 13.5

**Width of a cardboard box [cm]:** 25

**Height of a cardboard box [cm]:** 19

## 39386 KMB10-C25/1

---

Overcurrent circuit breaker, 1P

Length of a cardboard box [cm] : 46

Volume of a cardboard box [m<sup>3</sup>] : 0.02185