


39387 KMB10-C25/2

Miniature circuit breaker, 2P

5905339393876



PRODUCT PARAMETERS:

Rated voltage [V]: 230/400 AC

Rated frequency [Hz]: 50

Rated current [A]: 25

Place of assembly: na szynę TH35

IP class: 20

Norm: PN-EN 60898-1

Length [mm]: 76

Width [mm]: 35

Height [mm]: 82

Ambient temperature range to which the product can be exposed: -5÷40

Range of sections of wires used [mm²]: 1÷25

Terminal capacity – solid conductor [mm²]: max 25

Terminal capacity – stranded conductor [mm²]: max 16

Release characteristics: C

Energy-limit class: 3

Number of modules: 2

Rated short-circuit current [A]: 10000

Rated insulation voltage UI [V]: 500

Number of poles: 2

Mechanical endurance: 10000

Electrical endurance: 4000

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 60

Number of units in the secondary packaging: 60

Number of units in the packaging: 60

Net unit weight [g]: 218

Grammage [g]: 235

Gross unit weight [g]: 218

Length of a unit pack [cm]: 3.5

Width of a unit pack [cm]: 7.2

Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 14.1

Width of a cardboard box [cm]: 25

Height of a cardboard box [cm]: 19

39387 KMB10-C25/2

Miniature circuit breaker, 2P

Length of a cardboard box [cm] : 46

Volume of a cardboard box [m³] : 0.02185