

## 39401 KCS-63A/2P

Installation switch

5905339394019



### PRODUCT PARAMETERS

Rated voltage [V]	230/400 AC
Rated frequency [Hz]	50
Rated current [A]	63
Utilisation category	AC-22A
Place of application	Indoors
IP class	20
Norm	PN-EN 60947-3
Control type	mechaniczne
Number of modules	2
Tightening force [Nm]	1,2
Electrical endurance	2000
Number of poles	2 (6)

### DIMENSIONS AND MOUNTING

Height [mm]	88.5
Width [mm]	35.2

### MATERIAL AND CONSTRUCTION

Ambient temperature range to which the product can be exposed	-25+40
---	--------

Date of issue: 27.03.2026, 09:13

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

**DIMENSIONS AND MOUNTING**

Length [mm]	<b>76</b>
Connection type	<b>Terminal block</b>
Range of sections of wires used [mm <sup>2</sup> ]	<b>max 16</b>

**LOGISTICS**

Unit of measurement	<b>unit</b>
Packaging method	<b>120</b>
Number of units in the packaging	<b>120</b>
Net unit weight [g]	<b>144</b>
Grammage [g]	<b>169.33</b>
Gross unit weight [g]	<b>164</b>
Length of a unit pack [cm]	<b>10</b>
Width of a unit pack [cm]	<b>4</b>
Height of a unit pack [cm]	<b>8.5</b>
Weight of a cardboard box [kg]	<b>20.3196</b>
Width of a cardboard box [cm]	<b>26</b>
Height of a cardboard box [cm]	<b>37</b>
Length of a cardboard box [cm]	<b>52</b>
Volume of a cardboard box [m <sup>3</sup> ]	<b>0.050024</b>

Date of issue: 27.03.2026, 09:13

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com