

Kanlux



EAN: 5905339395245

CV power supply unit
Kanlux 39524 TRETO IP67 48V 150W



Date of issue: 08.04.2026, 07:51

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN

PRODUCT PARAMETERS

Rated voltage [V]	220-240 AC
Rated frequency [Hz]	50
Rated current [A]	max 1
Rated power [W]	75-150
Maximum power [W]	150
Place of application	Indoors and outdoors
IP class	67
Compatible with a dimmer	no
Power supply efficiency [%]	89
λ	0,9
Wire diameter [mm ²]	PRI: 1 / SEC: 1,5
Supply-cord type	constant-voltage
Output circuit type	SELV
Overload protection	yes
Short-circuit protection	yes
Maximum temperature Ta [°C]	45
Input voltage - PRI [V]	220-240
Output voltage - SEC [V]	48 DC
Output current - sec [ma]	max 3125
Tc [°C]	85

DIMENSIONS AND MOUNTING

Height [mm]	37
Width [mm]	52
Length [mm]	193
Wire length [m]	0.19
Possibility of installation on a normally flammable surface	yes
Connection type	Free cable ends

MATERIAL AND CONSTRUCTION

Colour	white
Material	plastic
Class of protection against electric shock	II

LOGISTICS

Unit of measurement	unit
Packaging method	20
Number of units in the secondary packaging	1
Number of units in the packaging	20
Net unit weight [g]	616
Grammage [g]	685
Gross unit weight [g]	666
Length of a unit pack [cm]	26
Width of a unit pack [cm]	6
Height of a unit pack [cm]	5.5
Weight of a cardboard box [kg]	13.7
Width of a cardboard box [cm]	28.5
Height of a cardboard box [cm]	26.5
Length of a cardboard box [cm]	32.5
Volume of a cardboard box [m ³]	0.024546

Date of issue: 08.04.2026, 07:51

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com