

# Kanlux



EAN: 5905339396273

Linear LED luminaire  
KANLUX 39627 VR-MH-NW-MAT-BRW-NT



Date of issue: 13.08.2026, 08:34

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland [kanlux@kanlux.com](mailto:kanlux@kanlux.com)


EN

## PRODUCT PARAMETERS

|                                                                 |                                                                                                               |
|-----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Rated voltage [V]                                               | 220-240 AC                                                                                                    |
| Rated frequency [Hz]                                            | 50                                                                                                            |
| Maximum power [W]                                               | 40                                                                                                            |
| Luminous flux [lm]                                              | 4900                                                                                                          |
| Correlated colour temperature [K]                               | 4000                                                                                                          |
| Colour consistency in McAdam ellipses                           | ≤3                                                                                                            |
| Colour temperature                                              | white                                                                                                         |
| Luminous efficiency of the lamp [lm/W]                          | 123                                                                                                           |
| Lighting angle [°]                                              | X85/Y95                                                                                                       |
| Diode type                                                      | LED SMD                                                                                                       |
| Integrated LED light source                                     | yes                                                                                                           |
| Colour rendering index                                          | 80                                                                                                            |
| Service life [h]                                                | 50000                                                                                                         |
| Luminous-flux-retention factor at the end of rated service life | L90B10                                                                                                        |
| Number of on/off cycles                                         | ≥30000                                                                                                        |
| Place of application                                            | Indoors                                                                                                       |
| IP class                                                        | 20                                                                                                            |
| Compatible with a dimmer                                        | no                                                                                                            |
| Fixture lighting direction                                      | down                                                                                                          |
| UGR                                                             | <22                                                                                                           |
| LED light source replaceability                                 | Possibility of replacing the LED light source only by qualified personnel (only by the manufacturer service)  |
| Control gear replaceability                                     | Possibility of replacing the control equipment only by qualified personnel (only by the manufacturer service) |
| Product category according to 2019/2020/EU                      | Containing product (CP)                                                                                       |

## DIMENSIONS AND MOUNTING

|                                       |                     |
|---------------------------------------|---------------------|
| Height [mm]                           | 99                  |
| Width [mm]                            | 60                  |
| Length [mm]                           | 1132                |
| Place of assembly                     | ceiling mounted     |
| Connection type                       | Self-clamping block |
| Range of sections of wires used [mm²] | 1,5÷2,5             |



## MATERIAL AND CONSTRUCTION

|                                              |                |
|----------------------------------------------|----------------|
| Colour                                       | brązowe drewno |
| Enclosure material                           | aluminum alloy |
| Lampshade material                           | plastic        |
| Shade type                                   | matt           |
| Class of protection against electric shock   | I              |
| Kształt                                      | rectangular    |
| Minimum distance from the illuminated object | 0,5m           |

## LIGHT SOURCE PARAMETERS

|                                                            |                  |
|------------------------------------------------------------|------------------|
| Useful luminous flux of the light source $\Phi_{use}$ [lm] | in sphere (360°) |
|------------------------------------------------------------|------------------|

## LOGISTICS

|                                            |      |
|--------------------------------------------|------|
| Unit of measurement                        | unit |
| Packaging method                           | 1    |
| Number of units in the secondary packaging | 1    |
| Number of units in the packaging           | 1    |
| Net unit weight [g]                        | 2976 |

Date of issue: 13.08.2026, 08:34

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

## MATERIAL AND CONSTRUCTION

Ambient temperature range to which  
the product can be exposed

5÷25