

## 45758 KMB6-P-50/1

Ogranicznik mocy umownej



### PRODUCT PARAMETERS

Rated voltage [V]	230/400 AC
Rated frequency [Hz]	50
Rated current [A]	50
IP class	20
Norm	PN-EN 60898-1
Number of fields	1
Terminal capacity – solid conductor [mm <sup>2</sup> ]	max 25
Terminal capacity – stranded conductor [mm <sup>2</sup> ]	max 16
Energy-limit class	3
Number of modules	1
Rated short-circuit current [A]	6000
Rated insulation voltage UI [V]	500
Number of poles	1
Mechanical endurance	10000
Electrical endurance	4000

Date of issue: 18.02.2026, 09:34

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

**DIMENSIONS AND MOUNTING**

Height [mm]	82
Width [mm]	18
Length [mm]	76
Place of assembly	na szynę TH35
Range of sections of wires used [mm <sup>2</sup> ]	1÷25

**MATERIAL AND CONSTRUCTION**

Ambient temperature range to which the product can be exposed	-5÷40
---	-------

**LOGISTICS**

Unit of measurement	unit
Packaging method	10
Number of units in the secondary packaging	10
Number of units in the packaging	120
Net unit weight [g]	95
Grammage [g]	104.08
Gross unit weight [g]	95
Length of a unit pack [cm]	2
Width of a unit pack [cm]	7.2
Height of a unit pack [cm]	8.5
Weight of a cardboard box [kg]	12.4896
Width of a cardboard box [cm]	24
Height of a cardboard box [cm]	19
Length of a cardboard box [cm]	46
Volume of a cardboard box [m <sup>3</sup> ]	0.020976

Date of issue: 18.02.2026, 09:34

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com