

45772 KRD10-2/25/100-F

Residual-current circuit breaker, 2P



PRODUCT PARAMETERS			
Rated voltage [V]		230 AC	
Rated frequency [Hz]		50	
Rated current [A]		25	
Differential-rated current [mA]		100	
Residual-current protection type		F	
IP class		20	
Norm		PN-EN 61008-1	
Terminal capacity – solid conductor [mm²]		max 25	
Terminal capacity – stranded conductor [mm²]		max 16	
Number of modules		2	
Rated activation capacity[A]		10000	
Rated insulation voltage UI [V]		400	
Number of poles		2	
DIMENSIONS AND MOUNTING		MATERIAL AND CONSTRUCTION	
Height [mm]	81	Colour	white
Width [mm]	36		

DIMENSIONS AND MOUNTING	
Length [mm]	75
Place of assembly	na szynę TH35
Range of sections of wires used [mm²]	max 25

MATERIAL AND CONSTRUCTION	
Ambient temperature range to which the product can be exposed	-25÷40

LOGISTICS	
Unit of measurement	unit
Packaging method	60
Number of units in the secondary packaging	1
Number of units in the packaging	60
Net unit weight [g]	210
Grammage [g]	236.67
Gross unit weight [g]	230
Length of a unit pack [cm]	9
Width of a unit pack [cm]	4.5
Height of a unit pack [cm]	8.5
Weight of a cardboard box [kg]	14.2002
Width of a cardboard box [cm]	27
Height of a cardboard box [cm]	19
Length of a cardboard box [cm]	49
Volume of a cardboard box [m³]	0.025137

Date of issue: 23.02.2026, 08:11

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com