

Kanlux



EAN: 5905339902740

Garden light fitting with replaceable light source
Kanlux 46204 RADIOLO 50 B



IP
44



Date of issue: 14.04.2026, 08:50

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN

PRODUCT PARAMETERS

Rated voltage [V]	220-240 AC
Rated frequency [Hz]	50
Maximum power [W]	max 11
Cap (Light source)	GU10
Light source	PARI6 LED
Light source included	no
Place of application	Indoors and outdoors
IP class	44
Fixture lighting direction	down

DIMENSIONS AND MOUNTING

Height [mm]	500
Width [mm]	105
Length [mm]	125
Place of assembly	On the floor
Connection type	Bolt terminal block
Range of sections of wires used [mm ²]	1÷1,5

MATERIAL AND CONSTRUCTION

Colour	black
Material	aluminum alloy, PC
Enclosure material	aluminum alloy
Lampshade material	PC
Class of protection against electric shock	I
Minimum distance from the illuminated object	0,2m
Ambient temperature range to which the product can be exposed	-20÷35

LOGISTICS

Unit of measurement	unit
Packaging method	6
Number of units in the secondary packaging	1
Number of units in the packaging	6
Net unit weight [g]	800
Grammage [g]	1043.33
Gross unit weight [g]	956
Length of a unit pack [cm]	13.5
Width of a unit pack [cm]	11.5
Height of a unit pack [cm]	51
Weight of a cardboard box [kg]	6.25998
Width of a cardboard box [cm]	37
Height of a cardboard box [cm]	29
Length of a cardboard box [cm]	53
Volume of a cardboard box [m ³]	0.056869

Date of issue: 14.04.2026, 08:50

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com