


70942 CYKLON EOL120P

Ducted fan

8594056490387



Kanlux CYKLON EOL series of fans is available in three sizes with diameter of 100, 120 and 150mm. They are made of plastic, in white colour. Their power is 19, 20 and 22W respectively. The number of rotations from each size comes to 2550/min.

PRODUCT PARAMETERS:

Colour: white

Place of assembly: Recessed mount in the wall

Place of application: Indoors

Off switch: yes

Length [mm]: 162

Width [mm]: 103

Height [mm]: 150

Assembly hole [mm]: Ø120

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 20

Class of protection against electric shock: II

Engine rotation: 2550

Bearing type: sliding

Connection type: Terminal block

Range of sections of wires used [mm²]: 1

Sound pressure [dB]: 38

Air-flow volume rate [m³/h]: 150

Motor-power consumption [W]: 20

IP class: X4

Protection class: II

LOGISTIC DATA:

Packaging method: 12

Number of units in the packaging: 12

Net unit weight [g]: 540

Grammage [g]: 675

Length of a unit pack [cm]: 16

Width of a unit pack [cm]: 10.5

Height of a unit pack [cm]: 17

Weight of a cardboard box [kg]: 8.1

Width of a cardboard box [cm]: 33

Height of a cardboard box [cm]: 33.5

Length of a cardboard box [cm]: 35

Volume of a cardboard box [m³]: 0.038693

ADDITIONAL INFORMATION:



70942 CYKLON EOL120P

Ducted fan

- Rotation speed: 2550/min
- Efficiency 150m³/h
- Noise level 38dB (A)
- CYKLON EOL120HT, additionally equipped with a moisture sensor which allows the fan to activate after reaching a pre-set moisture threshold