



**07281 ROGER DL-2LED6**

In-ground fixture

5905339072818



Kanlux ROGER DL is a ground-recessed luminaire with a built-in LED module. The specific shape of the shade distributes light evenly, which produces a unique light effect. The luminaire has a very high rating of tightness (IP66) and resistance to mechanical damage (IK09).

**PRODUCT PARAMETERS:****Colour:** grey**Place of assembly:** In the ground**Place of application:** Indoors and outdoors**Minimum distance from the illuminated object:** 0,1m**Compatible with a dimmer:** no**Fixture lighting direction:** horizontal**Height [mm]:** 74**Diameter [mm]:** 100**Number of chokes:** 1**Integrated LED light source:** yes**Rated voltage [V]:** 220-240 AC**Rated frequency [Hz]:** 50**Maximum power [W]:** 1**Class of protection against electric shock:** I**Diode type:** LED DIP**Colour temperature:** cold white**Service life [h]:** 20000**Ambient temperature range to which the product can be exposed:** -20÷35**Enclosure material:** steel**Panel/frame material:** aluminum alloy**Protective glass material:** plastic**Connection type:** Free cable ends**Wire length [m]:** 0.3**Wire diameter [mm<sup>2</sup>]:** 0,75**Lamp-heating time [s]:** ≤1**Lamp-ignition time [s]:** ≤0,5**Permissible static pressure [kN]:** 5**IK class:** 09**IP class:** 66**PARAMETERS FOR LED AND OLED LIGHT SOURCES:****Correlated colour temperature [K]:** 6000-6500

**07281 ROGER DL-2LED6**

In-ground fixture

**LOGISTIC DATA:****Packaging method:** 24**Number of units in the secondary packaging:** 1**Number of units in the packaging:** 24**Net unit weight [g]:** 270**Grammage [g]:** 333.33**Length of a unit pack [cm]:** 10**Width of a unit pack [cm]:** 10.5**Height of a unit pack [cm]:** 9**Weight of a cardboard box [kg]:** 7.99992**Width of a cardboard box [cm]:** 22**Height of a cardboard box [cm]:** 37**Length of a cardboard box [cm]:** 32**Volume of a cardboard box [m<sup>3</sup>]:** 0.026048**ADDITIONAL INFORMATION:**

- Junction box included

KANLUX S.A. (kat 7281) ROGER DL-2LED6 / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 7281) ROGER DL-2LED6

Lampy: 1 x ROGER DL-2LED6

