


08500 J-120W 118MM STAR

Halide light source

5905339085009



The designed halogen bulbs are intended for lamps and halopaks with R7s thread. Available power from 80W to 400W. They are meant for horizontal work.

TYPE OF LIGHT SOURCE:

Lighting technology used: HL

Non-directional or directional light source : NDLS

Mains or non-mains light source : MLS

Connected light source (CLS): no

Colour-tuneable light source: no

High luminance light source: no

Anti-glare shield : no

Dimmable: yes

PRODUCT PARAMETERS:

Width [mm]: 8

Height [mm]: 118

Depth [mm]: 8

Diameter [mm]: 8

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Rated power [W]: 120

Total rated luminous flux [lm]: 2220

Lampshade material: glass

Colour temperature: Warm white

Cap: R7s

Rated lamp-service life [h] : 2000

Number of on/off cycles : ≥ 8000

Additional information: Light source (LS)

Mercury content: no

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

Energy consumption in on-mode of the light source
(kWh/1000h): 120

Energy efficiency class: G

Useful luminous flux of the light source Φ_{use} [lm] : 2230

Useful luminous flux of the light source Φ_{use} [lm] : in sphere
(360°)

Correlated colour temperature [K] : 2700


On-mode power of the light source P_{on} [W] : 120

Colour rendering index: 100

Chromaticity coordinates (x): 0.458

08500 J-120W 118MM STAR

Halide light source



Chromaticity coordinates (y): 0.41

Claim of equivalent power [W]: 138

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 50

Number of units in the secondary packaging : 50

Number of units in the packaging : 500

Net unit weight [g] : 8

Grammage [g] : 14.8

Length of a unit pack [cm] : 2.5

Width of a unit pack [cm] : 2.5

Height of a unit pack [cm] : 13.5

Weight of a cardboard box [kg] : 7.4

Width of a cardboard box [cm] : 30

Height of a cardboard box [cm] : 27

Length of a cardboard box [cm] : 63

Volume of a cardboard box [m³] : 0.05103

ADDITIONAL INFORMATION:

- 23% more light flux by 20% lower power consumption (compared to F class halogen)
- designed for horizontal operation, allowable deflection of working position +/-4°

