

90120 KDB-IP65-S04T MK2

KDB-series distribution board


5905339901200



PRODUCT PARAMETERS			
Rated voltage [V]		690 AC; 1500 DC	
Place of application		Indoors and outdoors	
IP class		65	
IK class		08	
Norm		PN-EN 62208	
Number of modules		4P	
number of rows		1	

DIMENSIONS AND MOUNTING		MATERIAL AND CONSTRUCTION	
Height [mm]	200	Colour	grey
Width [mm]	103	Class of protection against electric shock	II
Length [mm]	128	Ambient temperature range to which the product can be exposed	-25+40
Place of assembly	wall mounted		

RYSUNKI WYMIAROW



SYMBOL	A	B	C
KDB-IP65-S04T MK2	128	200	103
KDB-IP65-S06T MK2	164	200	103
KDB-IP65-S09T MK2	218	200	103
KDB-IP65-S13T MK2	296	230	121
KDB-IP65-S18T MK2	386	230	121
KDB-IP65-S26T MK2	296	390	131
KDB-IP65-S39T MK2	296	550	131
KDB-IP65-S09T MK2+	218	200	103
KDB-IP65-S18T MK2+	386	230	121
KDB-IP65-S39T MK2+	296	550	131

LOGISTICS

Unit of measurement	unit
Packaging method	40
Number of units in the secondary packaging	1
Number of units in the packaging	40
Net unit weight [g]	534
Grammage [g]	647.5
Gross unit weight [g]	616
Length of a unit pack [cm]	13.5
Width of a unit pack [cm]	11
Height of a unit pack [cm]	21
Weight of a cardboard box [kg]	25.9
Width of a cardboard box [cm]	44
Height of a cardboard box [cm]	56
Length of a cardboard box [cm]	55
Volume of a cardboard box [m ³]	0.13552

Date of issue: 10.08.2026, 13:45

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com